

43



5

METHODS OF MANUFACTURING REAGENT TEST STRIPS

10

INTRODUCTION

Field of Invention

The field of this invention is analyte determination, and is particularly directed to reagent test strips for use in analyte determination assays.

15

Background of the Invention

Analyte detection in physiological fluids, e.g., blood or blood-derived products, is of ever increasing importance to today's society. Analyte detection assays find use in a variety of applications, including clinical laboratory testing, home testing, *etc.*, where the results of such testing play a prominent role in the diagnosis and management of a variety of conditions. The more common analytes include glucose, alcohol, formaldehyde, L-glutamic acid, glycerol, galactose, glycated proteins, creatinine, ketone body, ascorbic acid, lactic acid, leucine, malic acid, pyruvic acid, uric acid and steroids, *etc.* In response to this growing importance of analyte detection, a variety of analyte detection protocols and devices for both clinical and home use have been developed.

25

Many current analyte detection protocols employ a reagent test strip to detect an analyte in a sample. With reagent test strips, a sample is applied to a reagent area of a small strip and a signal is produced that is indicative of the presence of analyte in the sample. As the demand for such test strips has grown, the need for ever more efficient test strip manufacturing protocols that minimize the waste of expensive materials has increased.

As such, there is continued interest in the development of new manufacturing methods that would increase the efficiency of manufacturing reagent test strips. Of particular interest would be manufacturing methods that provide for increased manufacturing efficiency, reduced cost and are amenable to continuous manufacture procedures.

Relevant Literature

U.S. Patents of interest include: 5,067,309. Also of interest are U.S. Patent Nos. 5,972,294; 5,968,836; 5,843,691; 5,789,255; 5,753,452; 5,620,863; 5,605,837; 5,563,042; 5,462,032; 5,418,142; 5,059,394; 5,179,005.

SUMMARY OF THE INVENTION

Methods for making reagent test strips are provided. In the subject methods, a test strip precursor made up of an elongated support material having a planar surface and a narrow strip of reagent material positioned along its central axis is cut according to an inter-digitating pattern to produce the plurality of reagent test strips. The initial precursor material may be a tape or in the form of a card or analogous shape. Also provided are the reagent test strips produced by the subject methods and kits that include the same. The subject reagent test strips and kits find use in analyte detection and/or concentration determination assays.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 provides a top view illustration of a test strip precursor with an inter-digitating pattern superimposed thereon.

Figures 2 to 8 provide top view illustrations of various reagent test strip configurations.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Methods for making reagent test strips are provided. In the subject methods, a test strip precursor made up of an elongated support material having a planar surface and a narrow strip of reagent material positioned along its central axis is cut according to an inter-digitating pattern to produce the plurality of reagent test strips. The initial precursor material may be a tape or in the form of a card or analogous shape. Also provided are the reagent test

strips produced by the subject methods and kits that include the same. The subject reagent test strips and kits find use in analyte detection and/or concentration determination assays. In further describing the invention, the subject methods of manufacture are described first, followed by a description of exemplary embodiments of reagent test strips produced by the methods, representative applications of use of the reagent test strips, and kits that include the subject reagent test strips.

Before the subject invention is described further, it is to be understood that the invention is not limited to the particular embodiments of the invention described below, as variations of the particular embodiments may be made and still fall within the scope of the appended claims. It is also to be understood that the terminology employed in this description is for the purpose of describing particular embodiments, and is not intended to be limiting. Instead, the scope of the present invention will be established by the appended claims.

In this specification and appended claims, singular references include the plural, unless the context clearly dictates otherwise. Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this invention belongs.

METHODS OF MANUFACTURE

As summarized above, the present invention provides methods of manufacturing reagent test strips. By reagent test strip is meant an article of manufacture that includes a support material and a reagent material, where the strip includes at least two domains, a handling domain and a sample application domain, where the reagent material is present only in the sample application domain. Exemplary reagent test strips that may be produced using the subject methods are described in greater detail, infra.

In the subject methods, the first step is to provide a test strip precursor. By test strip precursor is meant an elongated support material having a first planar surface and a narrow stripe of reagent material positioned on the central axis of the first planar surface. The test strip precursor may be in the form of a continuous tape or be in the form of a card, e.g., a parallelogram or analogous shape, of shorter length. As such, the length of the test strip precursor may vary considerably, depending on whether it is in the form of a tape or has a shorter shape, e.g., is in the form of a card. The width of the test strip precursor may also vary depending on the nature of the particular test strip being manufactured. In general the width of the test strip precursor may range from about 0.80 to 4.0 inches, usually from about 1.20 to 3.0 inches and more usually from about 1.6 to 2.8 inches; where in certain embodiments the width of the test strip precursor may range from about 2.40 to 4.0 inches, usually from about 2.5 to 3.2 and more usually from about 2.6 to 2.8 and in other embodiments the width of the test strip precursor may range from about 0.8 to 3.0, usually from about 1.2 to 2.5 inches and more usually from about 1.5 to 2.0 inches.

As mentioned above, the test strip precursor is made up of an elongated support material that has a narrow reagent strip positioned on a planar surface of the inert support material. As such, the elongated support material has dimensions that are the same as the dimensions of the test strip precursor in terms of length and width, as described above. The solid support component of the test strip blank provides physical form and rigidity to the strip, among other features. The solid support of the test strip blank may be fabricated from a variety of materials, where suitable materials that may be employed as the substrate include plastics, e.g. PET, PETG, polyimide, polycarbonate, polystyrene, nylon, silicon, ceramic, glass, and the like; paper, plastic paper laminate, metallic sheets or any other suitable material, including a composite material of a support coated with a metallic and/or conductive coating which acts as an electrode (such as palladium, gold, platinum, silver, iridium, carbon (conductive carbon ink), doped tin oxide, stainless steel, e.g., where the strip is an electrochemical test strip. For examples of support materials that find use in certain embodiments of the subject invention, see e.g., the support materials disclosed in U.S. Patent

Nos. 4,935,346 and 5,304,468, the disclosures of which are herein incorporated by reference.

Positioned on one of the planar surfaces of the elongated support material, e.g., the top or bottom surface depending on the particular vantage point, is a narrow strip of reagent material. The narrow stripe of reagent material is generally positioned along the central longitudinal axis of the elongated support material. By central longitudinal axis is meant the center axis that is equidistant from each side of the support material. Generally, the two sides of the narrow reagent stripe are equidistant from the corresponding adjacent edge of the elongated support material.

The reagent material that is present in the narrow reagent stripe of the reagent strip precursor includes one or more specific reagent members of a signal producing system. By signal producing system is meant one or more reagents which work in combination to provide a detectable signal in the presence of an analyte that can be used to determine the presence and/or concentration of analyte. The signal producing system may be a signal producing system that produces a color that can be related to the presence or concentration of an analyte or it may be a signal producing system that produces an electrical current that can be related to the presence or concentration of an analyte. As such, the signal producing system may be a color producing system or a current producing system.

A variety of different color signal producing systems are known. Representative color signal producing systems of interest include analyte oxidation signal producing systems. By analyte oxidation signal producing system is meant that in generating the detectable colorimetric signal from which the analyte concentration in the sample is derived, the analyte is oxidized by a suitable enzyme to produce an oxidized form of the analyte and a corresponding or proportional amount of hydrogen peroxide. The hydrogen peroxide is then employed, in turn, to generate the detectable product from one or more indicator compounds, where the amount of detectable product produced by the signal producing system, *i.e.* the signal, is then related to the amount of analyte in the initial sample. As such, the analyte oxidation signal producing systems present in the subject test strips are also correctly characterized as hydrogen peroxide based signal producing systems.

As indicated above, the hydrogen peroxide based signal producing systems include an enzyme that oxidizes the analyte and produces a corresponding amount of hydrogen peroxide, where by corresponding amount is meant that the amount of hydrogen peroxide that is produced is proportional to the amount of analyte present in the sample. The specific nature of this first enzyme necessarily depends on the nature of the analyte being assayed but is generally an oxidase. As such, the first enzyme may be: glucose oxidase (where the analyte is glucose); cholesterol oxidase (where the analyte is cholesterol); alcohol oxidase (where the analyte is alcohol); lactate oxidase (where the analyte is lactate) and the like. Other oxidizing enzymes for use with these and other analytes of interest are known to those of skill in the art and may also be employed. In those embodiments where the reagent test strip is designed for the detection of glucose concentration, the first enzyme is glucose oxidase. The glucose oxidase may be obtained from any convenient source, *e.g.*, a naturally occurring source such as *Aspergillus niger* or *Penicillium*, or recombinantly produced.

The second enzyme of the signal producing system is an enzyme that catalyzes the conversion of one or more indicator compounds into a detectable product in the presence of hydrogen peroxide, where the amount of detectable product that is produced by this reaction is proportional to the amount of hydrogen peroxide that is present. This second enzyme is generally a peroxidase, where suitable peroxidases include: horseradish peroxidase (HRP), soy peroxidase, recombinantly produced peroxidase and synthetic analogs having peroxidative activity and the like. See *e.g.*, Y. Ci, F. Wang; *Analytica Chimica Acta*, 233 (1990), 299-302.

The indicator compound or compounds, *e.g.* substrates, are ones that are either formed or decomposed by the hydrogen peroxide in the presence of the peroxidase to produce an indicator dye that absorbs light in a predetermined wavelength range. Preferably the indicator dye absorbs strongly at a wavelength different from that at which the sample or the testing reagent absorbs strongly. The oxidized form of the indicator may be the colored, faintly-colored, or colorless final product that evidences a change in color. That is to say, the testing reagent can indicate the presence of analyte, *e.g.*, glucose, in a sample by a colored area being bleached or, alternatively, by a colorless area developing color.

Indicator compounds that are useful in the present invention include both one- and two-component colorimetric substrates. One-component systems include aromatic amines, aromatic alcohols, azines, and benzidines, such as tetramethyl benzidine-HCl. Suitable two-component systems include those in which one component is MBTH, an MBTH derivative (see for example those disclosed in U.S. patent application Ser. No. 08/302,575, incorporated herein by reference), or 4-aminoantipyrine and the other component is an aromatic amine, aromatic alcohol, conjugated amine, conjugated alcohol or aromatic or aliphatic aldehyde. Exemplary two-component systems are 3-methyl-2-benzothiazolinone hydrazone hydrochloride (MBTH) combined with 3-dimethylaminobenzoic acid (DMAB); MBTH combined with 3,5-dichloro-2-hydroxybenzene-sulfonic acid (DCHBS); and 3-methyl-2-benzothiazolinone hydrazone N-sulfonyl benzenesulfonate monosodium (MBTHSB) combined with 8-anilino-1 naphthalene sulfonic acid ammonium (ANS). In certain embodiments, the dye couple MBTHSB-ANS is preferred.

In yet other embodiments, signal producing systems that produce a fluorescent detectable product (or detectable non- fluorescent substance, e.g. in a fluorescent background) may be employed, such as those described in: Kiyoshi Zaito, Yosuke Ohkura: New fluorogenic substrates for Horseradish Peroxidase: rapid and sensitive assay for hydrogen peroxide and the Peroxidase. Analytical Biochemistry (1980) 109, 109-113.

As mentioned above, also of interest are signal producing systems that produce an electric current, e.g., as are employed in electrochemical test strips. Such reagent systems include redox reagent systems, which reagent systems provide for the species that is measured by the electrode and therefore is used to derive the concentration of analyte in a physiological sample. The redox reagent system present in the reaction area typically includes at least an enzyme(s) and a mediator. In many embodiments, the enzyme member(s) of the redox reagent system is an enzyme or plurality of enzymes that work in concert to oxidize the analyte of interest. In other words, the enzyme component of the redox reagent system is made up of a single analyte oxidizing enzyme or a collection of two or more enzymes that work in concert to oxidize the analyte of interest. Enzymes of interest include oxidases, dehydrogenases, lipases, kinases, diphosphatases, quinoproteins, and the like.

The specific enzyme present in the reaction area depends on the particular analyte for which the electrochemical test strip is designed to detect, where representative enzymes include: glucose oxidase, glucose dehydrogenase, cholesterol esterase, cholesterol oxidase, lipoprotein lipase, glycerol kinase, glycerol-3-phosphate oxidase, lactate oxidase, lactate dehydrogenase, pyruvate oxidase, alcohol oxidase, bilirubin oxidase, uricase, and the like. In many preferred embodiments where the analyte of interest is glucose, the enzyme component of the redox reagent system is a glucose oxidizing enzyme, e.g. a glucose oxidase or glucose dehydrogenase.

The second component of the redox reagent system is a mediator component, which is made up of one or more mediator agents. A variety of different mediator agents are known in the art and include: ferricyanide, phenazine ethosulphate, phenazine methosulfate, phenylenediamine, 1-methoxy-phenazine methosulfate, 2,6-dimethyl-1,4-benzoquinone, 2,5-dichloro-1,4-benzoquinone, ferrocene derivatives, osmium bipyridyl complexes, ruthenium complexes, and the like. In those embodiments where glucose is the analyte of interest and glucose oxidase or glucose dehydrogenase are the enzyme components, mediators of particular interest are ferricyanide, and the like.

Other reagents that may be present in the reaction area include buffering agents, e.g. citraconate, citrate, malic, maleic, phosphate, "Good" buffers and the like. Yet other agents that may be present include: divalent cations such as calcium chloride, and magnesium chloride; pyrroloquinoline quinone; types of surfactants such as Triton, Macol, Tetronic, Silwet, Zonyl, and Pluronic; stabilizing agents such as albumin, sucrose, trehalose, mannitol, and lactose.

Depending upon the particular nature of the signal producing system, the system may or may not be associated with a support matrix material. In these embodiments, the porous matrix is an inert porous matrix and acts as a support for the various members of the signal producing system. A number of different porous matrices have been developed for use in various analyte detection assays, which matrices differ in terms of materials, pore sizes, dimensions and the like, where representative matrices include those described in U.S. Patent Application Serial Nos.: 4,734,360; 4,900,666; 4,935,346; 5,059,394; 5,304,468;

5,306,623; 5,418,142; 5,426,032; 5,515,170; 5,526,120; 5,563,042; 5,620,863; 5,753,429; 5,573,452; 5,780,304; 5,789,255; 5,843,691; 5,846,486; 5,968,836 and 5,972,294; the disclosures of which are herein incorporated by reference. In principle, the nature of the porous matrix is not critical to the subject test strips and therefore is chosen with respect to other factors, including the nature of the instrument which is used to read the reagent test strip, convenience, type of assay to be performed with the reagent test strip, and the like.

As mentioned above, the reagent material, which may or may not include a supporting matrix as described above, is present on the reagent strip precursor as a narrow stripe that is positioned on one surface of the elongated support material and runs along the longitudinal axis of the support material. The width of the narrow reagent stripe may vary depending on the nature of the particular test strip being manufactured. In general the width of the narrow reagent stripe may range from about 0.05 to 0.50 inches, usually from about 0.10 to 0.4 inches and more usually from about 0.15 to 0.35 inches ; where in certain embodiments the width of the narrow reagent stripe may range from about 0.10 to 0.50 inches, usually from about 0.15 to 0.4 inches and more usually from about 0.18 to 0.35 inches and in other embodiments the width of the narrow reagent stripe may range from about 0.05 to 0.30 inches, usually from about 0.10 to 0.25 and more usually from about 0.15 to 0.20 inches.

The reagent strip precursor as described above may be produced using any convenient protocol. As such, the narrow reagent stripe can be laid down or attached to the support material along the central longitudinal axis, e.g., by joining two pieces, e.g., tapes, etc. A continuous process, e.g., one in which various rolls of material are brought together to produce the precursor (as is done in a continuous web process) or a discontinuous process, e.g., one in which the two strips are first cut and then joined to each other, may be employed. Other modes of strip precursor fabrication may also be employed.

The next step in the subject methods following provision of the reagent strip precursor, as described above, is to cut the precursor into a plurality of reagent test strips according to an inter-digitating pattern. By inter-digitating pattern is meant a pattern characterized by a series of inter-laced fingers or projections that are positioned along the

narrow reagent stripe. A representative inter-digitating pattern is shown in Fig. 1. As can be seen in Fig. 1, the test strip precursor is in the form of a card 100 which has elongated support material 110 with a narrow reagent stripe 120 positioned along its central axis such that it is equidistant from each side, i.e., x and y are the same length. Superimposed on the card 100 is an inter-digitating pattern of test strips, which is characterized by a series of continuous and oppositely oriented fingers or projections along the reagent strip and center axis. The inter-digitating pattern shown in Figure 1 is merely representative, where a number of inter-digitating patterns may be employed, as will be evident from the plurality of different test strip designs that are discussed infra.

Inter-digitating patterns employed in the subject methods are generally those that produce reagent test strips that include a sample region and a handling region, where the reagent material is located in the sample region. The respective areas of these two regions may vary, where the ratio of the areas of the two regions may range anywhere from about 0.05 to 0.95, usually from about 0.08 to 0.90 and more usually from about 0.10 to 0.92. Sample and handling regions are shown on the representative strips depicted in Figs. 1-8, where a dashed line separates the two regions, e.g. the 140 handling region and the 150 sample region in strip shown in Fig. 1. In many embodiments, the area of the sample region may range from about 0.01 to 0.60 square inches, usually from about 0.015 to 0.50 square inches and more usually from about 0.03 to 0.45 square inches; where in certain embodiments the area of the sample region may range from about 0.10 to 0.60 square inches, usually from about 0.20 to 0.50 square inches and more usually from about 0.25 to 0.45 square inches and in other embodiments the area of the sample region may range from about 0.01 to 0.25 square inches usually from about 0.015 to 0.15 square inches and more usually from about 0.02 to 0.10 square inches. In many embodiments, the area of the holding region may range from about 0.02 to 0.80 square inches, usually from about 0.08 to 0.70 square inches and more usually from about 0.10 to 0.65 square inches; where in certain embodiments the area of the holding region may range from about 0.30 to 0.80 square inches, usually from about 0.40 to 0.70 square inches and more usually from about 0.45 to 0.65 square inches and in other embodiments the area of the holding region may range from

about 0.02 to 0.30 square inches usually from about 0.08 to 0.25 square inches and more usually from about 0.10 to 0.20 square inches.

The ratio of the average width of the sample region to the average width of the handling region typically ranges from about 0.01 to 0.99, usually about 0.1 to 0.9 but is often about or is 0.5.

In other words, the inter-digitating pattern employed in the subject methods is generally one that provides for an aspect ratio of the sample region to handling/holding region ranges from about 0.1 to 0.9, where in certain embodiments an aspect ratio that is about 0.5 may be preferred. By aspect ratio is meant the ratio of the average width of the sample region to the average width of the holding domain, i.e., a to b in Figure 1.

As described above, the test strip precursor is cut according to an inter-digitating pattern. In other words, the precursor is singulated into the individual test strips according to an inter-digitating pattern. By cut is meant either automated or manual cutting, i.e., the test strip blank may be manually cut or cut using an automated means into the plurality of reagent test strips, e.g., with a laser singulation means, a rotary die cutting means, etc. The inter-digitating pattern may be in the form of a guide, map, image or other direction means that directs or indicates how the test strip precursor should be cut into the reagent test strips. The pattern may or may not be visual on the test strip blank prior to cutting/singulation. Where the pattern is visible, the image may be apparent from a complete outline, a partial outline, or designated points or markings of a strip.

REAGENT TEST STRIPS

Also provided by the subject invention are reagent test strips that are produced by the subject methods in which a test strip precursor is cut according to an inter-digitating pattern, as described above. The reagent test strips of the subject invention generally include a sample domain and a handling or holding domain, where the sample domain includes the reagent material, which may or may not include a support matrix, as described above.

The size of the reagent test strips cut from the test strip precursor may vary. In many

embodiments, the total area of a reagent test strip produced by the subject methods ranges from about 0.65 to 1.65 square inches, and usually from about 0.75 to 1.50 square inches. The length of a reagent test strip typically ranges from about 1.60 to 1.95 inches, and more typically from about 1.70 to 1.85. In many embodiments, the sample domain or region of the test strip has a hole located beneath the reagent material, so that a sample can be applied to one side of the reagent material and a color detected from the other side. In certain embodiments, the sections are joined together by a neck region, *e.g.*, either expanded or constricted. Configurations that may find use in the present invention are configurations substantially the same as or identical to a reagent test strip selected from the group of configurations shown in Figures 2 to 8, which are now described in further detail.

Figure 2 illustrates a top view of one embodiment of the reagent test strip. Reagent test strip 11 is comprised of two sections of differing size, a first or sample section 12 and a second or handling section 13. First section 12 is relatively smaller in size than second section 13, wherein second section 13 has an area ranging from about 0.50 to 0.75 square inches. The total area of reagent test strip 11 ranges from about 0.75 to 1.50 square inches and the total length 14 ranges from about 1.70 to 1.85 inches. Hole 15 is present in first section 12. Notch 16 is present on free edge 17 of first section 12, of which edges 18 and 19 are substantially straight.

Figure 3 illustrates a top view of another embodiment of the reagent test strip. Reagent test strip 20 is comprised of two sections of differing size, a first or sample section 21 and a second or handling section 22. First section 21 is relatively smaller in size than second section 22, wherein second section 22 has an area ranging from about 0.50 to 0.75 square inches. The total area of strip 20 ranges from about 0.75 to 1.50 square inches and the total length 23 ranges from about 1.70 to 1.85 inches. Hole 24 is present in first section 21. First section 21 is joined to second section 22 by constricted neck region 25. Lips 26 and 27 and notch 28 are on free edge 29 of first section 21.

A further embodiment of the reagent test strip is illustrated in Figure 4. Reagent test strip 30 is comprised of two sections of differing size, a first or sampling section 31 and a second or handling section 32. First section 31 is relatively smaller in size than second

section 32, wherein second section 32 has an area ranging from about 0.50 to 0.75 square inches. The total area of strip 30 ranges from about 0.75 to 1.50 square inches and the total length 33 ranges from about 1.70 to 1.85 inches. First section 31 has a width 34, such that width 34 progressively narrows towards free edge 35 of first section 31. Free edge 35 has notch 36 therein, of which top edges 37 and 38 of notch 36 are substantially straight. Hole 39 is present in first section 31. Width 40 of second section 32 is slightly greater than width 34 of first section 31, thereby creating shoulders 41 and 42 where first section 31 joins second section 32.

Figure 5 illustrates a top view of a further embodiment of the reagent test strip.

Reagent test strip 43 is comprised of two sections of differing size, a first sample section 44 and a second handling section 45. First section 44 is relatively smaller in size than second section 45, wherein second section 45 has an area ranging from about 0.50 to 0.75 square inches. The total area of strip 43 ranges from about 0.75 to 1.50 square inches and the total length 46 ranges from about 1.70 to 1.85 inches. Width 47 of first section 44 is greatest where first section 44 meets expanded neck region 48, and progressively narrows towards free edge 49 of first section 44. Free edge 49 of first section 44 has notch 50 therein, and is distally tapered, terminating in substantially pointed ends 52 and 53. Hole 54 is present in first section 44.

Figure 6 illustrates a top view of reagent test strip 55. Reagent test strip 55 is characterized by having two sections of differing size, a first or sample section 56 and a second or handling section 57. First section 56 is relatively smaller in size than second section 57, wherein second section 57 has an area ranging from about 0.50 to 0.75 square inches. The total area of reagent test strip 55 ranges from about 0.75 to 1.50 square inches and the total length 58 ranges from about 1.70 to 1.85 inches. Width 59 of first section 56 is widest in the area where first section 56 is joined to second section 57, and progressively narrows towards free edge 60 of first section 56. First section 56 is joined to second section 57 by expanded neck region 61, creating rounded shoulders 62 and 63. Free edge 60 of first section 56 has notch 64 therein, of which top edges 65 and 66 are substantially rounded. Hole 67 is present in first section 56.

Figure 7 illustrates a top view of another embodiment of the reagent test strip, reagent test strip 68. Reagent test strip 68 is characterized by having two sections of differing size, a first or sample section 69 and a second or handling section 70. First section 69 is relatively smaller in size than second section 70, wherein second section 70 has an area ranging from about 0.50 to 0.75 square inches. The total area of reagent test strip 68 ranges from about 0.75 to 1.50 square inches and the total length 71 ranges from about 1.70 to 1.85 inches. Width 72 of first section 69 is narrowest in the area where it meets neck region 73, and progressively widens towards free edge 74 of first section 69. First section 69 is joined to second section 70 by constricted neck region 73, where neck region 73 has substantially raised shoulders 75 and 76. Free edge 74 of first section 69 has a notch 77 therein, of which top edges 78 and 79 are substantially rounded. Hole 80 is present in first section 69.

Figure 8 illustrates reagent test strip 68 with first section 69 joined to second section 70 by constricted neck region 81, where neck region 81 has sloping shoulders 82 and 83.

In many embodiments of the subject methods, the reagent test strips produced by the subject methods can be employed with optical hand held meters. Of particular interest are optical hand held meters are described in U.S. Patent Nos. 4,935,346; 5,304, 468; 5,972,294; 5,179,005; 5,526,120; and 5,059,394, the disclosures of which are herein incorporated by reference. In many embodiments, the reagent strips produced by the subject methods can be read in a ONE TOUCH[®] meter as sold by Lifescan, Inc.

METHODS OF USE

Also provided by the subject invention are methods of using the subject reagent test strips to detect the presence of and/or determine the concentration of an analyte in a physiological sample. In these methods, the first step is to apply a sample suspected of containing the analyte of interest to the test strip, i.e., to the sample region of the test strip. Following the application of the sample to the test strip, the sample is allowed to react with the members of the signal producing system to produce a detectable product that is present

in an amount proportional to the initial amount present in the sample. The amount of detectable product, e.g., signal produced by the signal producing system, is then determined and related to the amount of analyte in the initial sample. The detection and relation steps can be accomplished by either direct observation with the eye or with an optical instrument, e.g., an optical instrument that detects changes in reflectance. In certain embodiments, handheld optical instruments that suitably perform the above mentioned detection and relation steps are of interest, as described in U.S. Patent Nos.: 4,935,346; 5,304,468; 5,972,294; 5,179,005; 5,526,120; 5,059,394; the disclosures of which are herein incorporated by reference, where a commercially available embodiment of such a meter is the ONE TOUCH[®] meter as sold by Lifescan, Inc.

A variety of different analytes may be detected using the subject reagent test strips, where representative analytes include glucose, cholesterol, lactate, alcohol, and the like. In many preferred embodiments, the subject methods are employed to determine the glucose concentration in a physiological sample. While in principle the subject methods may be used to determine the concentration of an analyte in a variety of different physiological samples, such as urine, tears, saliva, and the like, they are particularly suited for use in determining the concentration of an analyte in blood or blood fractions, e.g., blood derived samples, and more particularly in whole blood.

In practicing the subject methods, the first step is to apply a quantity of the physiological sample to the test strip, where the test strip is described *supra*. The amount of physiological sample, e.g., blood, that is applied to the test strip may vary, but generally ranges from about 0.2 μ L to 40 μ L, usually from 0.3 μ L to 20 μ L). Because of the nature of the subject test strip, where blood glucose concentration is of interest, the blood sample size that is applied to the test strip may be relatively small, ranging in size from about 2 μ L to 40 μ L, usually from about 5 μ L to 20 μ L. Where blood is the physiological sample, blood samples of a variety of hematocrits may be assayed with the subject methods, where the hematocrit may range from about 20% to 65%, usually from about 25% to 60%.

Following the application of the sample to the test strip, the sample is allowed to react with the members of the signal producing system to produce a detectable product that is present in an amount proportional to the initial amount present in the sample. The amount of detectable product, *i.e.*, signal produced by the signal producing system, is then

5 determined and related to the amount of analyte in the initial sample. The detection and relation steps can be accomplished by either direct observation with the eye or with a meter, *e.g.*, described in U.S. Patent Application Nos.: 4,734,360; 4,900,666; 4,935,346; 5,059,394; 5,304,468; 5,306,623; 5,418,142; 5,426,032; 5,515,170; 5,526,120; 5,563,042; 5,620,863; 5,753,429; 5,573,452; 5,780,304; 5,789,255; 5,843,691; 5,846,486; 5,968,836 and
10 5,972,294; the disclosures of which are herein incorporated by reference.

KITS

Also provided by the subject invention are kits for use in practicing the subject
15 invention. The kits of the subject invention at least include a reagent test strip, as described above. The subject kits may further include a means for obtaining a physiological sample. For example, where the physiological sample is blood, the subject kits may further include a means for obtaining a blood sample, such as a lance for sticking a finger, a lance actuation means, and the like. In addition, the subject kits may include a control solution or standard,
20 *e.g.*, a glucose control solution that contains a standardized concentration of glucose. In certain embodiments, the kits also include an optical instrument or meter, as described above, for detecting the amount of product produced on the strip following sample application and related the detected product to the amount of analyte in the sample, *e.g.*, a ONE TOUCH® meter. Finally, the kits include instructions for using the subject reagent test
25 strips in the determination of an analyte concentration in a physiological sample. These instructions may be present on one or more of the packaging, a label insert, containers present in the kits, and the like.

It is evident from the above discussion that the subject invention provides a highly efficient means of producing reagent test strips from a test strip blank. Using the subject methods, one can obtain a greater number of reagent test strips from a given amount of reagent material than can be achieved using previously known processes. Furthermore, the subject methods are adaptable to continuous web based processing protocols. As such, the subject invention represents a significant contribution to the art.

Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, it is readily apparent to those of ordinary skill in the art in light of the teachings of this invention that certain changes and modifications may be made thereto without departing from the spirit or scope of the appended claims.

All publications and patents cited in this specification are herein incorporated by reference as if each individual publication or patent were specifically and individually indicated to be incorporated by reference. The citation of any publication is for its disclosure prior to the filing date and should not be construed as an admission that the present invention is not entitled to antedate such publication by virtue of prior invention.

WHAT IS CLAIMED IS:

1. A method of manufacturing a plurality of reagent test strips, said method comprising:
 - 5 (a) providing a test strip precursor comprising an elongated support material having a first planar surface and a stripe of reagent material positioned along a central axis thereof; and
 - (b) cutting said test strip precursor into a plurality of reagent test strips according to an inter-digitating pattern.
- 10 2. The method according to Claim 1, wherein said test strip precursor is a tape.
3. The method according to Claim 1, wherein said test strip precursor is a card.
- 15 4. The method according to Claim 1, wherein said reagent material comprises a signal producing system.
5. The method according to Claim 4, wherein said signal producing system produces a color that can be related to the concentration of an analyte in a sample contacted with said
20 reagent material.
6. The method according to Claim 4, wherein said signal producing system produces an electrical current that can be related to the concentration of an analyte in a sample contacted with said reagent material.
- 25 7. The method according to Claim 1, wherein said method further comprises producing said test strip precursor.

8. The method according to Claim 1, wherein each of said strips produced by said method includes a sample region and a handling region, where said reagent material is located in said sample region.

9. The method according to Claim 8, wherein said sample region includes a hole in said support material which is covered by said reagent material.

10. The method according to Claim 8, wherein said strip has an aspect ratio that is about 0.5.

11. The method according to Claim 1, wherein said test strips produced by said method can be used in a hand-held optical meter.

12. The method according to Claim 1, wherein said hand-held optical meter is a ONE TOUCH[®] meter.

13. A reagent test strip produced according to the method of Claim 1, wherein said reagent test strip has a sample region and a handling region, wherein said reagent material is located in said sample region.

14. The reagent test strip according to Claim 13, wherein said reagent test strip has an aspect ratio of that is about 0.5.

15. The reagent test strip according to Claim 14, wherein said reagent test strip has a configuration that is substantially the same as or identical to a reagent test strip configuration selected from the group of configurations shown in Figures 2 to 8.

16. The reagent test strip according to Claim 15, wherein said reagent test strip can be read by a hand held optical meter.

17. The reagent test strip according to Claim 16, wherein said hand held optical meter is a ONE TOUCH[®] meter.

18. A method for determining the concentration of an analyte in a sample, said method comprising:

- (a) applying a fluid sample to a reagent test strip of Claim 13;
- (b) detecting a signal from said reagent test strip; and
- (c) relating said detected signal to the concentration of analyte in said sample to determine the concentration of said analyte in said fluid sample.

19. The method according to Claim 18, wherein said fluid sample is a biological sample.

20. The method according to Claim 18, wherein said analyte is glucose.

21. The method according to Claim 18, wherein said detecting and relating steps are performed by a hand held optical meter.

22. The method according to Claim 21, wherein said hand held optical meter is a ONE TOUCH[®] meter.

23. A kit for use in determining the concentration of an analyte in a physiological sample, said kit comprising:

- (a) a reagent test strip according to Claim 13; and
- (b) at least one of:
 - (i) a means for obtaining said physiological sample; and
 - (ii) an analyte standard.

24. The kit according to Claim 23, wherein said means for obtaining said physiological sample is a lance.

25. The kit according to Claim 23, wherein said analyte standard comprises a
5 standardized concentration of a known reagent.

26. The kit according to Claim 23, wherein said kit comprises said means for obtaining said physiological sample and said analyte standard.

10 27. The kit according to Claim 23, wherein said kit further comprises a hand held optical meter.

28. The kit according to Claim 27, wherein said hand held optical meter is a ONE TOUCH[®] meter.

ABSTRACT OF THE DISCLOSURE

Methods for making reagent test strips are provided. In the subject methods, a test strip precursor made up of an elongated support material having a planar surface and a narrow stripe of reagent material positioned along its central axis is cut according to an inter-digitating pattern to produce the plurality of reagent test strips. The initial precursor material may be a tape or in the form of a card. Also provided are the reagent test strips produced by the subject methods and kits that include the same. The subject reagent test strips and kits find use in analyte detection and/or concentration determination assays.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000